



Turner
1009 Plum



Turner
108 Wine



Turner
11 Brick



Turner
14 Rust



Turner
17 Garnet



Turner
205 Sprig




Turner
3003 Pacific Blue




Turner
3006 Navy




Turner
37 Lagoon




Turner
3822 White




Turner
3948 Taupe




Turner
54 Citron




Turner
6003 Cream




Turner
6009 Chinchilla




Turner
605 Parchment




Turner
608 Sandstone




Turner
61 Vanilla




Turner
802 Tan



Turner
8020 Chocolate




Turner
805 Bisque




Turner
808 Mocha




Turner
84 Earth




Turner
87 Chestnut



Turner
9003 Grey




Turner
9009 Black



Turner
905 Steel



Turner
95 Quicksilver



- Abrasion** Exceeds 500,000 Double Rubs.
- Backing Content** 30% Cotton 70% Polyester
- Cleaning Instruction** Mild soap and water. Dry immediately with a soft, dry cloth.
- Cold Crack** Product Cold Crack is equal to or greater than -40 degrees Celsius (-40 Fahrenheit)
- Colors Available** 27 colors available.
- Construction** Vinyl
 - Content** 100% Polyurethane (PU)
 - Crocking** AATCC 8: Dry = Class 5 AATCC 8: Wet = Class 5
 - Description** Simulated Leather Vinyl, Contract Rated
 - Eco Friendly** Eco-Friendly
 - Elongation** ASTM D5034: Warp: 23.4%, Fill: 38.1 %
Wipe with a soft cloth, with cold water and a mild soap. Dry immediately. Adhesion of Coating
 - Features** ASTM D751 Section 45-48 Warp = 7.34 lb/in and Weft = 5.06 lb/in.
Phthalate Free Hydrolysis pass 5 weeks (equal 5 years). PVC Free California Bulletin 117-Section E, Motor Vehicle Safety Standard 302.
 - Fire Retardancy** NFPA 260 Class 1. UFAC Class 1
 - Roll Size** 30 yards (27.4 m)
 - Seam Slippage** Passes Seam Slippage ASTM-D751. W 116 x F 90 lb.
 - Style** Solids / Plain
 - Tear Strength** Passes ASTM D2261 - Warp = 20 lbs and Fill = 12 lbs.
 - Tensile Strength** Passes ASTM D5034 - Warp = 105 lbs and Fill = 74 lbs.
 - Ultraviolet** Colorfastness to Light AATCC16 Class 4.5
 - Uses** Upholstery
 - Weight** 15.33 ounces per square yard.
23.00 Ounces per Linear Yard
 - Width** 54" (137 cm)

