

Turner  
1009 Plum



Turner  
108 Wine



Turner  
11 Brick



Turner  
14 Rust



Turner  
17 Garnet



Turner  
205 Sprig




Turner  
3003 Pacific Blue




Turner  
3006 Navy




Turner  
37 Lagoon




Turner  
3822 White




Turner  
3948 Taupe




Turner  
54 Citron




Turner  
6003 Cream




Turner  
6009 Chinchilla




Turner  
605 Parchment



Turner  
608 Sandstone



Turner  
61 Vanilla




Turner  
802 Tan



Turner  
8020 Chocolate




Turner  
805 Bisque



Turner  
808 Mocha




Turner  
84 Earth




Turner  
87 Chestnut




Turner  
9003 Grey




Turner  
9009 Black



Turner  
905 Steel



Turner  
95 Quicksilver



|                             |  |
|-----------------------------|--|
| <b>Abrasion</b>             | Exceeds 500,000 Double Rubs.   |
| <b>Backing Content</b>      | 30% Cotton 70% Polyester   |
| <b>Cleaning Instruction</b> | Mild soap and water. Dry immediately with a soft, dry cloth.   |
| <b>Cold Crack</b>           | Product Cold Crack is equal to or greater than -40 degrees Celsius (-40 Fahrenheit)  |
| <b>Colors Available</b>     | 27 colors available.   |
| <b>Construction</b>         | Vinyl  |
| <b>Content</b>              | 100% Polyurethane ( PU)  |
| <b>Crocking</b>             | AATCC 8: Dry = Class 5 AATCC 8: Wet = Class 5  |
| <b>Description</b>          | Simulated Leather Vinyl, Contract Rated  |
| <b>Eco Friendly</b>         | Eco-Friendly   |
| <b>Elongation</b>           | ASTM D5034: Warp: 23.4%, Fill: 38.1 %<br>Wipe with a soft cloth, with cold water and a mild soap. Dry immediately. Adhesion of Coating |
| <b>Features</b>             | ASTM D751 Section 45-48 Warp = 7.34 lb/in and Weft = 5.06 lb/in.<br>Phthalate Free Hydrolysis pass 5 weeks (equal 5 years). PVC Free   |
| <b>Fire Retardancy</b>      | California Bulletin 117-Section E, Motor Vehicle Safety Standard 302. NFPA 260 Class 1. UFAC Class 1                                   |
| <b>Roll Size</b>            | 30 yards (27.4 m)  |
| <b>Seam Slippage</b>        | Passes Seam Slippage ASTM-D751. W 116 x F 90 lb.   |
| <b>Style</b>                | Solids / Plain   |
| <b>Tear Strength</b>        | Passes ASTM D2261 - Warp = 20 lbs and Fill = 12 lbs.   |
| <b>Tensile Strength</b>     | Passes ASTM D5034 - Warp = 105 lbs and Fill = 74 lbs.  |
| <b>Ultraviolet</b>          | Colorfastness to Light AATCC16 Class 4.5   |
| <b>Uses</b>                 | Upholstery   |
| <b>Weight</b>               | 15.33 ounces per square yard.<br>23.00 Ounces per Linear Yard  |
| <b>Width</b>                | 54" (137 cm)   |

